

## CARGO MILER

The reliable tyre for long haul.

- 01. Designed for long haul applications and high loads
- 02. Multiple retreadability with strong casing
- 03. Better grip on wet road conditions



TYRE SIZE	PLY RATING	REC RIM WIDTH (CODE)	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	NON SKID DEPTH (MM)	LOAD / INFLATION		SPEED RATING	LOAD INDEX
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm		
8.25-20	12	6.5	235	975	13.1	2040 @ 7.0	1790 @ 7.0	J	133/128
8.25-20	14	6.5	235	975	13.1	2230 @ 8.1	1960 @ 7.4	J	136/132
8.25-20	16	6.5	235	975	13.1	2300 @ 8.4	2000 @ 7.75	J	137/132
9.00-20	14	7.0	261	1025	14.5	2570 @ 7.75	2255 @ 7.0	K	141/137
9.00-20	16	7.0	261	1025	14.5	2650 @ 8.1	2325 @ 7.4	J	142/137
10.00-20	16	7.5	280	1062	15.8	3000 @ 8.1	2630 @ 7.4	K	146/142
11.00-20	16	8.0	292	1084	16.1	3265 @ 8.1	2865 @ 7.4	J	150/145
12.00-20	18	8.5	308	1143	17.0	3725 @ 8.1	3265 @ 7.4	J	154/150
12.00-22.5	16	8.5	291	1076	16.0	3350 @ 8.1	2900 @ 7.4	K	150/145