

CARGO PLUS

The cooler-running tyres for high-speed operations.

- 01. Provides excellent traction and control
- 02. Excellent casing ensures high reliability and multiple treads
- 03. Long life and low heat generation at high speed



TYRE SIZE	PLY RATING	REC RIM WIDTH (CODE)	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	NON SKID DEPTH (MM)	LOAD / INFLATION		SPEED RATING	LOAD INDEX
						SINGLE Kgs@kgs/sq.cm	DUAL Kgs@kgs/sq.cm		
10.00-20	12	7.5	278	1057	13.3	2500 @ 6.0	2180 @ 5.3	K	140/135
10.00-20	14	7.5	278	1057	13.3	2740 @ 7.0	2405 @ 6.30	K	140/139
10.00-20	16	7.5	278	1057	13.3	3000 @ 8.1	2630 @ 7.4	K	146/142
11.00-22	16	8.0	291	1138	14.4	3550 @ 8.0	3075 @ 7.35	K	150/145
11.00-22.5	12	9.0	283	1056	13.4	2500 @ 6.0	2180 @ 5.3	K	140/135
11.00-22.5	16	9.0	283	1056	13.4	3000 @ 8.0	2650 @ 7.35	K	146/142