

## AMAZER 3G

Enjoy a long life.

01. Unique FEA-stimulated tyre cavity design delivers an optimised footprint, low heat build-up and more belt-edge durability
02. Superior stability at high speeds, shorter braking distance and increased durability
03. Reduced rolling resistance and lesser fuel consumption due to new generation design and technology
04. CAD-stimulated multi-pitch tread design means more acoustic comfort, a quieter and more enjoyable ride



TYRE SIZE (INCHES)	LOAD INDEX	SPEED RATING	OVERALL DIA (MM)	SECTION WIDTH (MM)	OVERALL ROLLING CIRCUMFERENCE (MM)	RECOMMENDED RIM	ALTERNATE RIM
145/70 R12	69	T	506	147	1543	4.5	4.0/5.0
145/80 R12	74	T	534	143	1629	4.0	4.5
145/70 R13	71	T	532	147	1623	4.5	4.0/5.0
155/70 R13	75	T	547	155	1668	4.5	4.0/5.0
155/80 R13	79	T	577	157	1760	4.5	4.0/5.0
145/80 R13	75	T	558	145	1702	4.0	4.5
155/65 R14	75	T	556	157	1696	4.5	4.0/5.0
135/70 R12	65	S	495	135	1510	4.0	4.5
155/65 R12	71	S	505	155	1540	4.0	4.5