

AMAZER XL

Standard performance. Long life.

- 01. S/T Speed Rated
- 02. Reinforced tyre construction for long life
- 03. Visual alignment indicator for detecting any misalignment wear in tyre
- 04. Specially designed for low noise



TYRE SIZE (INCHES)	LOAD INDEX	SPEED RATING	OVERALL DIA (MM)	SECTION WIDTH (MM)	OVERALL ROLLING CIRCUMFERENCE (MM)	RECOMMENDED RIM	ALTERNATE RIM
145 / 70R12	69	T	510	144	1556	4.0	4.5
155 / 70R12	73	T	522	157	1592	4.5	4.0 / 5.0
145 / 70R13	71	T	534	146	1629	4.0	4.5
145 / 80R13	75	T	563	145	1717	4.0	4.5
155 / 70R13	75	S	551	155	1681	4.5	4.0 / 5.0
155 / 80R13	78	T	576	154	1757	4.5	4.0 / 5.0
165 / 65R13	77	T	546	165	1665	4.5	4.0 / 5.0
165 / 70R13	79	T	568	165	1732	4.5	4.0 / 5.0
165 / 80R13	83	T	595	165	1815	4.5	4.0 / 5.0
175 / 70R13	82	T	575	175	1754	5.0	4.5 / 5.5
175 / 80R13	86	T	613	175	1870	5.0	4.5 / 5.5
185 / 60R13	80	T	553	186	1687	5.5	5.0 / 6.0
185 / 70R13	86	T	591	185	1803	5.5	5.0 / 6.0
165 / 80R14	85	T	618	169	1885	5.0	4.5 / 5.5
185 / 65R14	86	T	597	185	1821	5.5	5.5 / 6.0
185 / 70R14	88	T	617	187	1882	5.5	5.0 / 6.0
195 / 70R14	91	T	630	200	1922	6.0	5.5 / 6.5
165 / 80R15	86	T	644	165	1964	4.5	4.0 / 5.0