Endu® Mile LHT

LONGHAUL TRAILER

A high mileage longhaul trailer tire

M + S

LONG HAUL

SmartWay

7-YEAR WARRANTY

PERFORMANCE GUARANTEE

ROAD HAZARD WARRANTY

5-RIB TREAD

5 ribs and optimized footprint offers superior resistance to lateral scrub.

HIGH MILEAGE

Deep tread grooves and rib orientation with multiple stress relieving sipes ensure superior mileage.

UNIFORM WEAR

De-coupler groove technology for enhanced shoulder stability and uniform wear under severe drag & sway conditions.

RETREADABILITY



Exceptional casing durability providing multiple retreads.

PRODUCT CODE	SIZE	LI/ SS	PLY RATING/ LOAD RANGE	SEC-TION WIDTH (INCH)	OVERALL DIAMETER (INCH)	TIRE WEIGHT LBS	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOM-MENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	ROLLING CIRCUM-FERENCE (INCH)	REVS / MILE	LOAD DETAILS (LBS)	
													SINGLE	DUAL
2023605	295/75R22.5	144/141/L	14/G	11.3	39.8	103	12	18.7	9.00	8.25	121.8	518	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2023604	295/75R22.5	149/146/L	16/H	11.3	39.8	103	12	18.7	9.00	8.25	121.8	518	7160 lbs @ 123 psi	6610 lbs @ 123 psi
2023607	11R22.5	144/142/L	14/G	10.9	41.0	110	12	20.2	8.25	7.50	125.6	504	6175 lbs @ 105 PSI	5840 lbs @ 105 PSI
2023606	11R22.5	146/143/L	16/H	10.9	41.0	110	12	20.2	8.25	7.50	125.6	504	6610 lbs @ 120 PSI	6005 lbs @ 120 PSI
2023609	11R24.5	146/143/L	14/G	11.0	42.8	119	13	20.2	8.25	7.50	131.7	481	6610 lbs @ 105 psi	6005 lbs @ 105 psi
2023608	11R24.5	149/146/L	16/H	11.0	42.8	119	13	20.2	8.25	7.50	131.7	481	7160 lbs @ 120 psi	6610 lbs @ 120 psi

APOLLO TIRES (US) INC. 6 Concourse Parkway Building 6. Suite 2920. Atlanta, GA 30328
+1 (877) 234 0867 contact.us@apollotyres.com

apollo TIRES

Copyright © 2025 Apollo Tires