Endu® Combi RT

REGIONAL TRAILER

Copyright © 2025 Apollo Tires

The Endu®Combi RT is a multi life, free rolling trailer tire with high scrub resistance.

M + S

REGIONAL

7-YEAR WARRANTY

PERFORMANCE GUARANTEE

ROAD HAZARD WARRANTY

HIGH SCRUB RESISTANCE

Solid rounded shoulder rib optimized for high scrub trailer applications.

EVEN WEAR



Deep stress-relieving sipes helps in maintaining even wear and higher removal mileages.

LONGER TREAD LIFE



Long tread life from tough, cool-running tread compound, offering maximum resistance to excessive scrub.

MULTIPLE RETREADS



Combination of superior tread design with robust belt package for enhanced durability.

PRODUCT CODE	SIZE	LI/SS	PLY RATING/ LOAD RANGE	SECTION WIDTH (INCH)	OVERALL DIAMETER (INCH)	TIRE WEIGHT LBS	ORIGINAL TREAD DEPTH (1/32")	STATIC LOADED RADIUS (INCH)	RECOMMENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	ROLLING CIRCUMFERENCE (INCH)	REVS / MILE	LOAD DETAILS (LBS)	
													SINGLE	DUAL
2021600	215/75R17.5	135/133/K	16/H	8.4	30.3	69	17	13.8	6.00	6.75	92.1	679	4805 lbs @123 psi	4540 lbs @123 psi
2023615	235/75R17.5	143/141/K	18/J	9.3	31.5	77	17	14.3	6.75	7.50	97.0	653	6005 lbs @ 125 psi	5675 lbs @ 125 psi
2023616	245/70R17.5	143/141/K	18/J	9.8	31.1	75	17	14.2	7.50	6.75	95.7	662	6005 lbs @ 125 psi	5675 lbs @ 125 psi
2021610	295/75R22.5	144/141/L	14/G	11.4	40.0	116	16	18.7	9.00	8.25	121.8	513	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021609	295/75R22.5	149/146/L	16/H	11.4	40.0	116	16	18.7	9.00	8.25	121.8	513	7160 lbs @ 123 psi	6610 lbs @ 123 psi
2021605	11R22.5	144/142/L	14/G	11.1	40.9	121	16	19.3	8.25	7.50	126.1	504	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021604	11R22.5	146/143/L	16/H	11.1	40.9	121	16	19.3	8.25	7.50	126.1	504	6610 lbs @ 120 psi	6005 lbs @ 120 psi

APOLLO TIRES (US) INC. 6 Concourse Parkway Building 6. Suite 2920. Atlanta, GA 30328
+1 (877) 234 0867 contact.us@apollotyres.com

apollo TIRES